1.5 L, Model S1500 TLL SYR, NDL Sold Separately

1.5 L, Model S1500 TLL SYR, NDL Sold Separately



Part Number/REF: 86313 Unit Price: Quote Required

Specifications

| Volume | 1.5 L |
|--|--|
| Syringe Type | Gastight |
| Syringe Series | Super Syringe |
| Termination | PTFE Luer Lock (TLL) |
| Needle | Metal (N) or Kel-F |
| Gauge | No Needle Included |
| Point Style | No Needle Included |
| Needle Length | No Needle Included |
| Std. Needle Dead Volume | N/A |
| | |
| Fluid Path | Buna-N, Nickel plated brass, PTFE, Silicone |
| Fluid Path Autoclavable | Buna-N, Nickel plated brass, PTFE, Silicone |
| | |
| Autoclavable | No |
| Autoclavable Gas Sterilizable | No Yes |
| Autoclavable Gas Sterilizable Pressure | No Yes 30 psig (2.1 bar) |
| Autoclavable Gas Sterilizable Pressure Maximum Temperature | No Yes 30 psig (2.1 bar) 80°C / 176°F |
| Autoclavable Gas Sterilizable Pressure Maximum Temperature Minimum Temperature | No Yes 30 psig (2.1 bar) 80°C / 176°F 0°C / 32°F |
| Autoclavable Gas Sterilizable Pressure Maximum Temperature Minimum Temperature Barrel Inner Diameter | No Yes 30 psig (2.1 bar) 80°C / 176°F 0°C / 32°F 3.44 inches (87.4 mm) |

Accessories

| Part Number/REF | Description | Unit Price |
|-----------------|---|----------------|
| 18026 | TLL Connector \$0500 \$1000 \$1500 \$2000 | Quote Required |

of Hamilton Company or its licensors in the U.S. and/or other countries.