$250~\mu\text{L},\,\text{Model}\,\,1725~\text{RN}\,\,\text{SYR},\,\text{NDL}\,\,\text{Sold}\,\,\text{Separately}$

 $250~\mu\text{L},~\text{Model}~1725~\text{RN}~\text{SYR},~\text{NDL}~\text{Sold}~\text{Separately}$



Part Number/REF: 7657-01 Unit Price: Quote Required

Specifications

Volume	250 µL
Syringe Type	Gastight
Syringe Series	1700
Termination	Removable Needle (RN)
Needle	Large RN
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Std. Needle Dead Volume	N/A
Fluid Path	SST, borosilicate glass, PTFE
Fluid Path Autoclavable	SST, borosilicate glass, PTFE Yes
Autoclavable	Yes
Autoclavable Gas Sterilizable	Yes Yes
Autoclavable Gas Sterilizable Pressure	Yes Yes 500 psig (34.5 bar)
Autoclavable Gas Sterilizable Pressure Maximum Temperature	Yes Yes 500 psig (34.5 bar) 115°C / 239°F
Autoclavable Gas Sterilizable Pressure Maximum Temperature Minimum Temperature	Yes Yes 500 psig (34.5 bar) 115°C / 239°F 10°C / 50°F

Accessories

Part Number/REF	Description	Unit Price
1162-03	Plunger Assembly N RN 1725	Quote Required
30902	RN Nut	Quote Required
CAL7657-01	250 microL Model 1725 RN Calibrated SYR NDL Sold Separately	Quote Required

Accessories

1/3/2017 3:49 PM

© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.

2 of 2