$25~\mu\text{L},\,\text{Model}\,\,1802~\text{RN}\,\,\text{SYR},\,\text{NDL}\,\,\text{Sold}\,\,\text{Separately}$

 $25~\mu\text{L},~\text{Model}~1802~\text{RN}~\text{SYR},~\text{NDL}~\text{Sold}~\text{Separately}$



Part Number/REF: 7660-01 Unit Price: Quote Required

Specifications

Volume	25 μL
Syringe Type	Gastight
Syringe Series	1800
Termination	Removable Needle (RN)
Needle	Small RN
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Std. Needle Dead Volume	N/A
Fluid Path	SST, borosilicate glass, PTFE
Fluid Path Autoclavable	SST, borosilicate glass, PTFE Yes
Autoclavable	Yes
Autoclavable Gas Sterilizable	Yes Yes
Autoclavable Gas Sterilizable Pressure	Yes Yes 1000 psig (68.9 bar)
Autoclavable Gas Sterilizable Pressure Maximum Temperature	Yes Yes 1000 psig (68.9 bar) 115°C / 239°F
Autoclavable Gas Sterilizable Pressure Maximum Temperature Minimum Temperature	Yes Yes 1000 psig (68.9 bar) 115°C / 239°F 10°C / 50°F

Accessories

Part Number/REF	Description	Unit Price
1160-01	Plunger Assembly N RN 1802	Quote Required
30902	RN Nut	Quote Required
32135	Holder Assembly	Quote Required
32188	Glass Barrel RN 1802	Quote Required
CAL7660-01	25 microL Model 1802 RN Calibrated SYR NDL Sold Separately	Quote Required

1/5/2017 1:50 PM

Accessories



Chaney Reproducibility Adapter

This adapter is built for reproducible injections. The adjustable stop prevents plunger damage and is easy to install in your laboratory.



Small Hub Removable Needles

These needles are available in 18-34 gauges. The standard length is 2 inches. Custom lengths are from 0.375 to 12 inches.

© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.

2 of 2