

50 μ L, Model 1805 RN SYR, NDL Sold Separately

50 μ L, Model 1805 RN SYR, NDL Sold Separately



Part Number/REF: 7661-01

Unit Price: Quote Required

Specifications

Volume	50 μ L
Syringe Type	Gastight
Syringe Series	1800
Termination	Removable Needle (RN)
Needle	Small RN
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Std. Needle Dead Volume	N/A
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	Yes
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	115°C / 239°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.041 inches (1.03 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)
Sales Quantity	1 syringe per pack

Accessories

Part Number/REF	Description	Unit Price
1161-01	Plunger Assembly N RN 1805	Quote Required
30902	RN Nut	Quote Required
32135	Holder Assembly	Quote Required
32189	Glass Barrel RN 1805	Quote Required
CAL7661-01	50 microL Model 1805 RN Calibrated SYR NDL Sold Separately	Quote Required

Accessories



Chaney Reproducibility Adapter

This adapter is built for reproducible injections. The adjustable stop prevents plunger damage and is easy to install in your laboratory.



Small Hub Removable Needles

These needles are available in 18-34 gauges. The standard length is 2 inches. Custom lengths are from 0.375 to 12 inches.

© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.