

# 10 µL, Model 1701 N SYR, Cemented NDL, 26s ga, 2 in, point style 3

10 µL, Model 1701 N SYR, Cemented NDL, 26s ga, 2 in, point style 3



Part Number/REF: 80075

Unit Price: Quote Required

## Specifications

Volume	10 µL
Syringe Type	Gastight
Syringe Series	1700
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	26s gauge
Point Style	3
Needle Length	2 inch (51 mm)
Needle Inner Diameter	0.005 inches (0.13 mm)
Needle Outer Diameter	0.0187 inches (0.47 mm)
Std. Needle Dead Volume	0.64 µL
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	No
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.018 inches (0.460 mm)
Barrel Outer Diameter	0.260 inches (6.60 mm)
Sales Quantity	1 syringe per pack

## Accessories

Part Number/REF	Description	Unit Price
13205	Plunger Assembly N, RN, LT, LTN 1701	Quote Required
CAL80075	10 microL Model 1701 N Calibrated SYR Cemented NDL 26s ga 2 in point style 3	Quote Required

## Accessories




### Digital Syringes

Digital Syringes come complete with Hamilton syringes to form a device of the highest accuracy and precision.



### Chaney Reproducibility Adapter

This adapter is built for reproducible injections. The adjustable stop prevents plunger damage and is easy to install in your laboratory.



### Syringe Guide

The Syringe Guide is designed to protect plungers from being bent or damaged. This device fits on 700, 1700 and 7000 series syringes.



### PB600-1 Repeating Dispenser

The PB600-1 is a sampling device designed for repeated dispensing of equal volumes. The instrument delivers 1/50th of the syringe volume.

---

© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.