## $25~\mu\text{L},\,\text{Model}\,\,1702~\text{LT}\,\,\text{SYR},\,\text{NDL}\,\,\text{Sold}\,\,\text{Separately}$

25 μL, Model 1702 LT SYR, NDL Sold Separately



Part Number/REF: 80201 Unit Price: Quote Required

## Specifications

Volume	25 μL
Syringe Type	Gastight
Syringe Series	1700
Termination	Luer Tip (LT)
Needle	Kel-F Hub
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Std. Needle Dead Volume	N/A
Fluid Path	Borosilicate glass, PTFE
Fluid Path  Autoclavable	Borosilicate glass, PTFE  Yes to 115°C
Autoclavable	Yes to 115°C
Autoclavable  Gas Sterilizable	Yes to 115°C Yes
Autoclavable  Gas Sterilizable  Pressure	Yes to 115°C  Yes  1000 psig (68.9 bar)
Autoclavable  Gas Sterilizable  Pressure  Maximum Temperature	Yes to 115°C  Yes  1000 psig (68.9 bar)  115°C / 239°F
Autoclavable  Gas Sterilizable  Pressure  Maximum Temperature  Minimum Temperature	Yes to 115°C  Yes  1000 psig (68.9 bar)  115°C / 239°F  10°C / 50°F

## Accessories

Part Number/REF	Description	Unit Price
1122-01	1702 Plunger Assembly LT N RN C	Quote Required
CAL80201	25 μL, Model 1702 LT Calibrated SYR, NDL Sold Separately	Quote Required

## Accessories

1 of 2 1/3/2017 11:04 AM

© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.

2 of 2