

# 25 µL, Model 1702 SN SYR, Cemented NDL, Custom gauge, length, point style

25 µL, Model 1702 SN SYR, Cemented NDL, Custom gauge, length, point style



Part Number/REF: 80208  
Unit Price: Quote Required

## Custom Specifications

Custom Point Style	2
--------------------	---

## Specifications

Custom Needle Length	0.75 inch (19.1 mm)
Volume	25 µL
Syringe Type	Gastight
Syringe Series	1700
Termination	Cemented Needle Special (SN)
Needle	Cemented Needle
Std. Needle Dead Volume	N/A
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	No
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.029 inches (0.729 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)
Sales Quantity	1 syringe per pack
Custom Point Style	Custom Point Style
Custom Gauge	Custom Gauge

## Accessories


Part Number/REF	Description	Unit Price
1122-01	1702 Plunger Assembly LT N RN C	Quote Required

## Accessories



### Chaney Reproducibility Adapter

This adapter is built for reproducible injections. The adjustable stop prevents plunger damage and is easy to install in your laboratory.



### Syringe Guide

The Syringe Guide is designed to protect plungers from being bent or damaged. This device fits on 700, 1700 and 7000 series syringes.



### PB600-1 Repeating Dispenser

The PB600-1 is a sampling device designed for repeated dispensing of equal volumes. The instrument delivers 1/50th of the syringe volume.

---

© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.