

25 μ L, Model 1702 TLLX SYR, Instrument Syringe w/ Adjustable Stop

25 μ L, Model 1702 TLLX SYR, Instrument Syringe w/ Adjustable Stop



Part Number/REF: 80223

Unit Price: Quote Required

Specifications

Autoclavable	Yes
Volume	25 μ L
Syringe Type	Gastight
Syringe Series	1700
Termination	PTFE Luer Lock (TLL)
Needle	Metal (N) or Kel-F
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Std. Needle Dead Volume	N/A
Fluid Path	Borosilicate glass, PTFE
Plunger Style	Instrument Plunger Stop (X)
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	115°C / 239°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.029 inches (0.729 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)
Sales Quantity	1 syringe per pack

Accessories



Kel-F Hub Needles



Metal Hub Needles

© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.