

25 μ L, Model 1702 RN SYR, Small Removable NDL, 22s ga, 2 in, point style 2

25 μ L, Model 1702 RN SYR, Small Removable NDL, 22s ga, 2 in, point style 2



Part Number/REF: 80230
Unit Price: Quote Required

Specifications

Volume	25 μ L
Syringe Type	Gastight
Syringe Series	1700
Termination	Removable Needle (RN)
Needle	Small RN
Gauge	22s gauge
Point Style	2
Needle Length	2 inch (51 mm)
Needle Inner Diameter	0.0059 inches (0.15 mm)
Needle Outer Diameter	0.0283 inches (0.72 mm)
Std. Needle Dead Volume	1.13 μ L
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	Yes
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	115°C / 239°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.029 inches (0.729 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)
Sales Quantity	1 syringe per pack

Accessories

Part Number/REF	Description	Unit Price
7758-03	22s gauge Small Hub RN NDL 2 in point style 2 6PK	Quote Required
1122-01	1702 Plunger Assembly LT N RN C	Quote Required
30902	RN Nut	Quote Required
CAL80230	25 microL t Model 1702 RN Calibrated SYR Small Removable NDL 22s ga 2 in point style 2	Quote Required

Accessories



Digital Syringes

Digital Syringes come complete with Hamilton syringes to form a device of the highest accuracy and precision.



Chaney Reproducibility Adapter

This adapter is built for reproducible injections. The adjustable stop prevents plunger damage and is easy to install in your laboratory.



Syringe Guide

The Syringe Guide is designed to protect plungers from being bent or damaged. This device fits on 700, 1700 and 7000 series syringes.



PB600-1 Repeating Dispenser

The PB600-1 is a sampling device designed for repeated dispensing of equal volumes. The instrument delivers 1/50th of the syringe volume.

© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.