

# 25 $\mu$ L, Model 1702 N SYR, Cemented NDL, 22s ga, 2 in, point style 3

25  $\mu$ L, Model 1702 N SYR, Cemented NDL, 22s ga, 2 in, point style 3



Part Number/REF: 80275

Unit Price: Quote Required

## Specifications

Volume	25 $\mu$ L
Syringe Type	Gastight
Syringe Series	1700
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	22s gauge
Point Style	3
Needle Length	2 inch (51 mm)
Needle Inner Diameter	0.0059 inches (0.15 mm)
Needle Outer Diameter	0.0283 inches (0.72 mm)
Std. Needle Dead Volume	1.13 $\mu$ L
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	No
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.029 inches (0.729 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)
Sales Quantity	1 syringe per pack

## Accessories

Part Number/REF	Description	Unit Price
1122-01	1702 Plunger Assembly LT N RN C	Quote Required
CAL80275	25 microL r Model 1702 N Calibrated SYR Cemented NDL 22s ga 2 in point style 3	Quote Required

## Accessories




### Digital Syringes

Digital Syringes come complete with Hamilton syringes to form a device of the highest accuracy and precision.



### Chaney Reproducibility Adapter

This adapter is built for reproducible injections. The adjustable stop prevents plunger damage and is easy to install in your laboratory.



### Syringe Guide

The Syringe Guide is designed to protect plungers from being bent or damaged. This device fits on 700, 1700 and 7000 series syringes.



### PB600-1 Repeating Dispenser

The PB600-1 is a sampling device designed for repeated dispensing of equal volumes. The instrument delivers 1/50th of the syringe volume.

---

© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.