

25 μ L, Model 1702 N SYR, Cemented NDL, 22 ga, 2 in, point style 3

25 μ L, Model 1702 N SYR, Cemented NDL, 22 ga, 2 in, point style 3



Part Number/REF: 80285

Unit Price: Quote Required

Specifications

| | |
|-------------------------|-------------------------------|
| Volume | 25 μ L |
| Syringe Type | Gastight |
| Syringe Series | 1700 |
| Termination | Cemented Needle (N) |
| Needle | Cemented Needle |
| Gauge | 22 gauge |
| Point Style | 3 |
| Needle Length | 2 inch (51 mm) |
| Needle Inner Diameter | 0.0161 inches (0.41 mm) |
| Needle Outer Diameter | 0.0283 inches (0.72 mm) |
| Std. Needle Dead Volume | 6.81 μ L |
| Fluid Path | SST, borosilicate glass, PTFE |
| Autoclavable | No |
| Gas Sterilizable | Yes |
| Pressure | 1000 psig (68.9 bar) |
| Maximum Temperature | 50°C / 122°F |
| Minimum Temperature | 10°C / 50°F |
| Barrel Inner Diameter | 0.029 inches (0.729 mm) |
| Barrel Outer Diameter | 0.305 inches (7.75 mm) |
| Sales Quantity | 1 syringe per pack |

Accessories


| Part Number/REF | Description | Unit Price |
|-----------------|---------------------------------|----------------|
| 1122-01 | 1702 Plunger Assembly LT N RN C | Quote Required |

Accessories



Chaney Reproducibility Adapter

This adapter is built for reproducible injections. The adjustable stop prevents plunger damage and is easy to install in your laboratory.



Syringe Guide

The Syringe Guide is designed to protect plungers from being bent or damaged. This device fits on 700, 1700 and 7000 series syringes.



PB600-1 Repeating Dispenser

The PB600-1 is a sampling device designed for repeated dispensing of equal volumes. The instrument delivers 1/50th of the syringe volume.

© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.