

50 µL, Model 1705 SN SYR, Cemented NDL, Custom gauge, length, point style

50 µL, Model 1705 SN SYR, Cemented NDL, Custom gauge, length, point style



Part Number/REF: 80908
Unit Price: Quote Required

Custom Specifications

Custom Point Style	2
--------------------	---

Specifications

Custom Needle Length	0.75 inch (19.1 mm)
Volume	50 µL
Syringe Type	Gastight
Syringe Series	1700
Termination	Cemented Needle Special (SN)
Needle	Cemented Needle
Std. Needle Dead Volume	N/A
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	No
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.041 inches (1.03 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)
Sales Quantity	1 syringe per pack
Custom Point Style	Custom Point Style
Custom Gauge	Custom Gauge

Accessories

Part Number/REF	Description	Unit Price
1162-01	Plunger Assembly N RN LTLTN SampleLock TLL w wo Slots 1705	Quote Required

Accessories



Chaney Reproducibility Adapter

This adapter is built for reproducible injections. The adjustable stop prevents plunger damage and is easy to install in your laboratory.



Syringe Guide

The Syringe Guide is designed to protect plungers from being bent or damaged. This device fits on 700, 1700 and 7000 series syringes.



PB600-1 Repeating Dispenser

The PB600-1 is a sampling device designed for repeated dispensing of equal volumes. The instrument delivers 1/50th of the syringe volume.