

50 µL, Model 1705 RN SYR, Small Removable NDL, 22s ga, 2 in, point style 3

50 µL, Model 1705 RN SYR, Small Removable NDL, 22s ga, 2 in, point style 3



Part Number/REF: 80965
Unit Price: Quote Required

Specifications

Volume	50 µL
Syringe Type	Gastight
Syringe Series	1700
Termination	Removable Needle (RN)
Needle	Small RN
Gauge	22s gauge
Point Style	3
Needle Length	2 inch (51 mm)
Needle Inner Diameter	0.0059 inches (0.15 mm)
Needle Outer Diameter	0.0283 inches (0.72 mm)
Std. Needle Dead Volume	1.13 µL
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	Yes
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	115°C / 239°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.041 inches (1.03 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)
Sales Quantity	1 syringe per pack

Accessories

Part Number/REF	Description	Unit Price
7770-01	22s gauge Small Hub RN NDL 2 in point style 3 6PK	Quote Required
1162-01	Plunger Assembly N RN LTLN SampleLock TLL w wo Slots 1705	Quote Required
30902	RN Nut	Quote Required

Accessories



Chaney Reproducibility Adapter

This adapter is built for reproducible injections. The adjustable stop prevents plunger damage and is easy to install in your laboratory.



Syringe Guide

The Syringe Guide is designed to protect plungers from being bent or damaged. This device fits on 700, 1700 and 7000 series syringes.



PB600-1 Repeating Dispenser

The PB600-1 is a sampling device designed for repeated dispensing of equal volumes. The instrument delivers 1/50th of the syringe volume.



Small Hub Removable Needles

These needles are available in 18-34 gauges. The standard length is 2 inches. Custom lengths are from 0.375 to 12 inches.