

50 μ L, Model 1705 N SYR, Cemented NDL, 22s ga, 2 in, point style 3

50 μ L, Model 1705 N SYR, Cemented NDL, 22s ga, 2 in, point style 3



Part Number/REF: 80975

Unit Price: Quote Required

Specifications

Volume	50 μ L
Syringe Type	Gastight
Syringe Series	1700
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	22s gauge
Point Style	3
Needle Length	2 inch (51 mm)
Needle Inner Diameter	0.0059 inches (0.15 mm)
Needle Outer Diameter	0.0283 inches (0.72 mm)
Std. Needle Dead Volume	1.13 μ L
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	No
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.041 inches (1.03 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)
Sales Quantity	1 syringe per pack

Accessories

Part Number/REF	Description	Unit Price
1162-01	Plunger Assembly N RN LTLTN SampleLock TLL w wo Slots 1705	Quote Required
CAL80975	50 microL Model 1705 N Calibrated SYR Cemented NDL 22s ga 2 in point style 3	Quote Required

Accessories




Digital Syringes

Digital Syringes come complete with Hamilton syringes to form a device of the highest accuracy and precision.



Chaney Reproducibility Adapter

This adapter is built for reproducible injections. The adjustable stop prevents plunger damage and is easy to install in your laboratory.



Syringe Guide

The Syringe Guide is designed to protect plungers from being bent or damaged. This device fits on 700, 1700 and 7000 series syringes.



PB600-1 Repeating Dispenser

The PB600-1 is a sampling device designed for repeated dispensing of equal volumes. The instrument delivers 1/50th of the syringe volume.

© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.