

250 µL, Model 1725 TLLX SYR, Instrument Syringe

250 µL, Model 1725 TLLX SYR, Instrument Syringe



Part Number/REF: 81122

Unit Price: Quote Required


Specifications

Volume	250 µL
Syringe Type	Gastight
Syringe Series	1700
Termination	PTFE Luer Lock (TLL)
Needle	Metal (N) or Kel-F
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Std. Needle Dead Volume	N/A
Fluid Path	Borosilicate glass, PTFE
Plunger Style	Instrument Plunger Stop (X)
Autoclavable	Yes
Gas Sterilizable	Yes
Pressure	500 psig (34.5 bar)
Maximum Temperature	115°C / 239°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.091 inches (2.30 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)
Sales Quantity	1 syringe per pack

Accessories

Part Number/REF	Description	Unit Price
1117-03	Plunger Assembly TLLXDXCX 1725	Quote Required

Accessories



© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.