

250 μ L, Model 1725 LTN SYR, Cemented NDL, 22 ga, 2 in, point style 3

250 μ L, Model 1725 LTN SYR, Cemented NDL, 22 ga, 2 in, point style 3



Part Number/REF: 81185

Unit Price: Quote Required

Specifications

Volume	250 μ L
Syringe Type	Gastight
Syringe Series	1700
Termination	Luer Tip Cemented Needle (LTN)
Needle	Cemented Needle
Gauge	22 gauge
Point Style	3
Needle Length	2 inch (51 mm)
Needle Inner Diameter	0.0161 inches (0.41 mm)
Needle Outer Diameter	0.0283 inches (0.72 mm)
Std. Needle Dead Volume	6.81 μ L
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	No
Gas Sterilizable	Yes
Pressure	500 psig (34.5 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.091 inches (2.30 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)
Sales Quantity	1 syringe per pack

Accessories


Part Number/REF	Description	Unit Price
1162-03	Plunger Assembly N RN 1725	Quote Required

Accessories



Chaney Reproducibility Adapter

This adapter is built for reproducible injections. The adjustable stop prevents plunger damage and is easy to install in your laboratory.



Syringe Guide

The Syringe Guide is designed to protect plungers from being bent or damaged. This device fits on 700, 1700 and 7000 series syringes.



PB600-1 Repeating Dispenser

The PB600-1 is a sampling device designed for repeated dispensing of equal volumes. The instrument delivers 1/50th of the syringe volume.

© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.