

500 µL, Model 1750 LTSN SYR, Cemented NDL, Custom gauge, length, point style

500 µL, Model 1750 LTSN SYR, Cemented NDL, Custom gauge, length, point style



Part Number/REF: 81214
Unit Price: Quote Required

Custom Specifications

Custom Point Style	2
--------------------	---

Specifications

Custom Needle Length	0.75 inch (19.1 mm)
Volume	500 µL
Syringe Type	Gastight
Syringe Series	1700
Termination	Luer Tip Cemented Needle Special (LTSN)
Needle	Cemented Needle
Std. Needle Dead Volume	N/A
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	No
Gas Sterilizable	Yes
Pressure	700 psig (48.3 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.128 inches (3.26 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)
Sales Quantity	1 syringe per pack
Custom Gauge	Custom Gauge
Custom Point Style	Custom Point Style

Accessories


Part Number/REF	Description	Unit Price
1169-01	Plunger Assembly N RN 1750	Quote Required

Accessories



Chaney Reproducibility Adapter

This adapter is built for reproducible injections. The adjustable stop prevents plunger damage and is easy to install in your laboratory.



Syringe Guide

The Syringe Guide is designed to protect plungers from being bent or damaged. This device fits on 700, 1700 and 7000 series syringes.



PB600-1 Repeating Dispenser

The PB600-1 is a sampling device designed for repeated dispensing of equal volumes. The instrument delivers 1/50th of the syringe volume.

© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.