500 µL, Model 1750 RN SYR, Large Removable NDL, 22 ga, 2 in, point style 2

 $500~\mu\text{L},~\text{Model}~1750~\text{RN}~\text{SYR},~\text{Large}~\text{Removable}~\text{NDL},~22~\text{ga},~2~\text{in, point}~\text{style}~2$



Specifications

Volume	500 μL
Syringe Type	Gastight
Syringe Series	1700
Termination	Removable Needle (RN)
Needle	Large RN
Gauge	22 gauge
Point Style	2
Needle Length	2 inch (51 mm)
Needle Inner Diameter	0.0161 inches (0.41 mm)
Needle Outer Diameter	0.0283 inches (0.72 mm)
Std. Needle Dead Volume	6.81 µL
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	Yes
Gas Sterilizable	Yes
Pressure	700 psig (48.3 bar)
Maximum Temperature	115°C / 239°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.128 inches (3.26 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)
Sales Quantity	1 syringe per pack

Accessories

Description	Unit Price
22 gauge Large Hub RN NDL 2 in point style 2 6PK	Quote Required
Plunger Assembly N RN 1750	Quote Required
RN Nut	Quote Required
500 microL Model 1750 RN Calibrated SYR Large Removable NDL 22 ga 2 in point style 2	Quote Required
	Plunger Assembly N RN 1750 RN Nut

1/5/2017 11:27 AM

Accessories



Digital Syringes

Digital Syringes come complete with Hamilton syringes to form a device of the highest accuracy and precision.



Chaney Reproducibility Adapter

This adapter is built for reproducible injections. The adjustable stop prevents plunger damage and is easy to install in your laboratory.



Syringe Guide

The Syringe Guide is designed to protect plungers from being bent or damaged. This device fits on 700, 1700 and 7000 series syringes.



PB600-1 Repeating Dispenser

The PB600-1 is a sampling device designed for repeated dispensing of equal volumes. The instrument delivers 1/50th of the syringe volume.

© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.

2 of 2