

1 mL, Model 1001 LTN SYR, Cemented NDL, 22 ga, 2 in, point style 2

1 mL, Model 1001 LTN SYR, Cemented NDL, 22 ga, 2 in, point style 2



Part Number/REF: 81317

Unit Price: Quote Required

Specifications

Volume	1 mL
Syringe Type	Gastight
Syringe Series	1000
Termination	Luer Tip Cemented Needle (LTN)
Needle	Cemented Needle
Gauge	22 gauge
Point Style	2
Needle Length	2 inch (51 mm)
Needle Inner Diameter	0.0161 inches (0.41 mm)
Needle Outer Diameter	0.0283 inches (0.72 mm)
Std. Needle Dead Volume	6.81 µL
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	No
Gas Sterilizable	Yes
Pressure	200 psig (13.8 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.181 inches (4.61 mm)
Barrel Outer Diameter	0.355 inches (9.02 mm)
Sales Quantity	1 syringe per pack

Accessories

Part Number/REF	Description	Unit Price
1359-01	Plunger Assembly LTLTNTLL w wo Slots SampleLock C 1001	Quote Required
CAL81317	1 mL Model 1001 LTN Calibrated SYR Cemented NDL 22 ga 2 in point style 2	Quote Required

Accessories



PB600-1 Repeating Dispenser

The PB600-1 is a sampling device designed for repeated dispensing of equal volumes. The instrument delivers 1/50th of the syringe volume.

© 2016 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.