

5 mL, Model 1005 LTN SYR, Cemented NDL, 22 ga, 2 in, point style 3

5 mL, Model 1005 LTN SYR, Cemented NDL, 22 ga, 2 in, point style 3



Part Number/REF: 81516

Unit Price: Quote Required

Specifications

Volume	5 mL
Syringe Type	Gastight
Syringe Series	1000
Termination	Luer Tip Cemented Needle (LTN)
Needle	Cemented Needle
Gauge	22 gauge
Point Style	3
Needle Length	2 inch (51 mm)
Needle Inner Diameter	0.0161 inches (0.41 mm)
Needle Outer Diameter	0.0283 inches (0.72 mm)
Std. Needle Dead Volume	6.81 μ L
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	No
Gas Sterilizable	Yes
Pressure	200 psig (13.8 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.406 inches (10.3 mm)
Barrel Outer Diameter	0.530 inches (13.5 mm)
Sales Quantity	1 syringe per pack

Accessories

Part Number/REF	Description	Unit Price
13230	Plunger Assembly LTLTNTLL w wo Slots RN 1005	Quote Required

CAL81516

5 mL Model 1005 LTN Calibrated SYR Cemented NDL 22 ga 2 in point style 3

Quote Required

© 2016 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.