

# 25 mL, Model 1025 TLL SYR, NDL Sold Separately

25 mL, Model 1025 TLL SYR, NDL Sold Separately



Part Number/REF: 82520

Unit Price: Quote Required

## Specifications

Fluid Path	Borosilicate glass, PTFE, PCTFE
Volume	25 mL
Syringe Type	Gastight
Syringe Series	1000
Termination	PTFE Luer Lock (TLL)
Needle	Metal (N) or Kel-F
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Std. Needle Dead Volume	N/A
Autoclavable	No
Gas Sterilizable	Yes
Pressure	100 psig (6.9 bar)
Maximum Temperature	80°C / 176°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.907 inches (23.0 mm)
Barrel Outer Diameter	1.07 inches (27.1 mm)
Sales Quantity	1 syringe per pack

## Accessories

Part Number/REF	Description	Unit Price
13271	Plunger Assembly LTLTNTLL w wo Slots ADDAD 1025	Quote Required
CAL82520	25 mL Model 1025 TLL Calibrated SYR NDL Sold Separately	Quote Required

## Accessories

© 2016 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.