

50 μ L, Model 1805 N SYR, Cemented NDL, 22s ga, 2 in, point style 2

50 μ L, Model 1805 N SYR, Cemented NDL, 22s ga, 2 in, point style 2



Part Number/REF: 84881

Unit Price: Quote Required

Specifications

Volume	50 μ L
Syringe Type	Gastight
Syringe Series	1800
Termination	Cemented Needle (N)
Needle	Cemented Needle
Gauge	22s gauge
Point Style	2
Needle Length	2 inch (51 mm)
Needle Inner Diameter	0.0059 inches (0.15 mm)
Needle Outer Diameter	0.0283 inches (0.72 mm)
Std. Needle Dead Volume	1.13 μ L
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	No
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	50°C / 122°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.029 inches (0.729 mm)
Barrel Outer Diameter	0.305 inches (7.75 mm)
Sales Quantity	1 syringe per pack

Accessories

Part Number/REF	Description	Unit Price
1161-01	Plunger Assembly N RN 1805	Quote Required
32135	Holder Assembly	Quote Required
CAL84881	50 microLa Model 1805 N Calibrated SYR Cemented NDL 22s ga 2 in point style 2	Quote Required

Accessories



Chaney Reproducibility Adapter

This adapter is built for reproducible injections. The adjustable stop prevents plunger damage and is easy to install in your laboratory.

© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.