

50 mL, Model 1050 TLL SYR, NDL Sold Separately

50 mL, Model 1050 TLL SYR, NDL Sold Separately



Part Number/REF: 85020

Unit Price: Quote Required

Specifications

Fluid Path	Borosilicate glass, PTFE, PCTFE
Volume	50 mL
Syringe Type	Gastight
Syringe Series	1000
Termination	PTFE Luer Lock (TLL)
Needle	Metal (N) or Kel-F
Gauge	No Needle Included
Point Style	No Needle Included
Needle Length	No Needle Included
Std. Needle Dead Volume	N/A
Autoclavable	No
Gas Sterilizable	Yes
Pressure	100 psig (6.9 bar)
Maximum Temperature	80°C / 176°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	1.28 inches (32.6 mm)
Barrel Outer Diameter	1.45 inches (36.9 mm)
Sales Quantity	1 syringe per pack

Accessories

Part Number/REF	Description	Unit Price
13272	Plunger Assembly LTLTNTLL w wo Slots 1050	Quote Required
CAL85020	50 mL a Model 1050 TLL Calibrated SYR NDL Sold Separately	Quote Required

Accessories

© 2017 Hamilton Company. All rights reserved. Hamilton Company, product and/or service names referenced are either trademarks or registered trademarks of Hamilton Company or its licensors in the U.S. and/or other countries.